

Fixture Height: 2 in. (5.08 cm)

Project:	
Type:	

## Model: FL50 (Flood Light)

Fixture Width: 4 in. (10.16 cm) Fixture Depth: 2.25 in. (5.71 cm) Base Height: 1.5 in. (3.81 cm) 4 in. (10.16 cm) -2 in. (5.08 cm) 1.5 in. (3.81 cm)

#### Specifications and Features:

Body: Brass fixture, aged brass finish

Knuckle: Solid brass knuckle with dial adjustment

Face plate: Brass face plate with rubber gasket attached to fixture with 4 screws

Lens: Clear lens

Socket: Spring loaded ceramic bi-pin socket with dual contact

Wire: Industry First, double wire lead pre-connected to the fixture, 16 awg (UL listed), brown

-25 foot wire lead, pre-stripped for easy wire connection

-18 inch wire lead, LED connection ready

Stake: Plastic ground stake, attached to the fixture (8.5 in; 21.6 cm length)

Warranty: Lifetime warranty on fixture housing

Certification: Complies with the requirements of UL-1838 and CAN/CSA-C22.2 No. 250.7. Identified with the ETL and cETL Listed Mark.



#### Lamp Options

Model #	Base Type	Wattage	Lumen Output	
LBIPIN-LED-3W	Bipin/G4	3w	150lm	
LXELOGEN-20 (Halogen)	Bipin/G4	20w	150lm	

LED Ordering Guide: Model-LED

Example: FL50-LED

#### Accessories Available:


Mounting Accessories:	FL100 Accessories
RISER6 - 6" brass riser, aged brass finish	Hex Louver
RISER12 - 12" brass riser, aged brass finish	
RISER18 - 18" brass riser, aged brass finish	
RISERADJ - Adjustable plastic riser, aged brass cap	
RMB - Round Mounting Base	
GUTTERMOUNT	

Notes:



Project:	
Type:	

# Model: LBIPIN-LED-3W (3 watt BIPIN LED)



### Specifications and Features:

Watts: 3

Base Type: G4/BiPin Light Output: 150 lumens Color: Warm White Color Temperatures: 2700K Operating Voltage: 8-24v

CRI: Ra>80

LED Chip Qty: 18 Pieces Halogen Equivalent: 20w Rated Hours: 50,000 hrs

Ambient Operating Temperature: <72°C

Transformer Compatibility: Must be powered by magnetic transformer

Warranty: Five year limited warranty on LED components

### Lamp Color Options

I	Model #	Color	Color Temp.	Base Type	Wattage	Lumen Output
l	LBIPINLED-3W-3K	Bright White	3000K	BIPIN/G4	3w	150lm
l	LBIPIN-LED-3W-AMBER*	Amber	Amber	BIPIN/G4	3w	150lm

<sup>\*</sup>Turtle Safe

Notes: