

Туре: ____

Model:

Project: _

MODEL: GL150 | MR16 IN-GROUND LIGHT

Small professional-grade in-ground light. MR16 lamp purchased separately. Open convex lens ideal for wall washing and directional uplighting. PVC sleeve included for stabilizing into the ground. Core-drill for placement into hardscapes or dig a small hole into softscapes. Not intended to be submerged or placed in wet areas. Ok for foot traffic, but not suitable for areas where they may be driven over by vehicles.

CONSTRUCTION: Cast brass housing base. Solid brass top with stainless steel screws.

FINISH: Classic aged brass or modern premium black overcoat.

LID: Flat open faced brass lid with clear convex glass lens. Attached with 4 color-matched stainless steel screws.

SOCKET: MR16, spring-loaded, ceramic, dual contacts, & lamp clips.

MOUNTING: Optional 2.75" PVC installation sleeve included.

WIRING: Pre-Installed dual 16AWG wire leads, primary 25' wire lead, and optional 18" wire lead for daisy chaining to other fixtures. Brown wire with aged brass finish, black wire with black overcoat.

WARRANTY: Lifetime warranty on fixture housing.

CERTIFICATIONS: Complies with the requirements of UL-1838 and CAN/CSA-C22.2 No. 250.7. Identified with the ETL & CETL Listed Mark.

DIMENSIONS:

Lid Diameter	3.5 inches
Lid Height	0.5 inches
Base Diameter	2.38 inches
Base Height	3.5 inches
Ship Weight	2.78 pounds





West Coast Hub: Temecula, CA • East Coast Hub: Sanford, FL Alliance Outdoor Lighting • (800) 930-6225 • www.allianceoutdoorlighting.com



MODEL: GL150 | MR16 IN-GROUND LIGHT

FINISH OPTIONS:

Aged Brass (Standard)	
Premium Black Overcoat (Add -BLK)	

MR16 LAMP OPTIONS:

ADD SUFFIX	WATTAGE	DELIVERED LUMENS	COLOR TEMP.
-LMR16-LED-4W-NS	4	250	2900K
-LMR16-LED-4W-F	4	250	2900K
-LMR16-LED-4W-WF	4	250	2900K
-LMR16-LED-4W-250Im	4	250	2900K
-LMR16-LED-4W-2700k	ά 4	250	2700K
-LMR16-LED-5W-NS	5	310	2900K
-LMR16-LED-5W-F*	5	310	2900K
-LMR16-LED-5W-WF	5	310	2900K
-LMR16-LED-5W-310Im	5	310	2900K
-LMR16-LED-5W-2700k	ς 5	310	2700K
-LMR16-LED-6W-F	6	410	2900K
-LMR16-LED-6W-2700k	6	410	2700K



* = standard light source option

HOW TO SPECIFY: Example: GL150-BLK-LED

FINISH	SUFFIX	ORDERING NUMBER	LAMP	ORDERING NUMBER
Aged Brass (Standard)		GL150	Add Lamp Suffix	GL150-LED
Premium Black Overcoat	-BLK	GL150-BLK		GL150-BLK-LED





West Coast Hub: Temecula, CA • East Coast Hub: Sanford, FL Alliance Outdoor Lighting • (800) 930-6225 • www.allianceoutdoorlighting.com 240501 Rev. 05/2024