

Pro Series

BULLET LIGHT



BL115
MR16

BL115-BLK
MR16

What's in the box?

The Pro Series Bullet Light is complete with Shroud, Lens, Stake and 36" Wire Lead

SPECIFICATIONS AND FEATURES:

- Body:** Solid brass with an aged brass finish (**BL115**)
Solid brass with premium black overcoat (**BL115-BLK**)
- Knuckle:** Solid brass with dial adjustment for easy adjustments
- Shroud:** Brass with a clear glass convex lens and double o-ring gasket
- Socket:** Spring loaded ceramic bi-pin socket with dual contact and lamp clips
- Wire:** 36 inch wire lead, 16 awg (UL listed), brown, Pre-connected to the fixture, Pre-stripped for easy wire connection
- Stake:** Plastic ground stake, attached to the fixture (8.5 in; 21.6 cm length)
- Warranty:** Lifetime warranty on fixture housing.

PATH LIGHTS



PAL105
G4/BIPIN

PAL705
G4/BIPIN

PAL105-BLK
G4/BIPIN

What's in the box?

The Pro Series Path Lights are complete with Stem, Hat, Lens, Stake and 36" Wire Lead

SPECIFICATIONS AND FEATURES:

- Hat:** Brass area light hat, aged brass finish (2-Tier Hat for PAL705)
Solid brass with premium black overcoat (**PAL105-BLK**)
- Lens:** Polycarbonate frosted lens with gaskets
- Stem:** Brass area light stem, aged brass finish
- Collar:** Aged brass finish
- Socket:** Spring loaded ceramic bi-pin socket with dual contact
- Wire:** 36 inch wire lead, 16 awg (UL listed), brown, Pre-connected to the fixture, Pre-stripped for easy wire connection
- Stake:** Plastic ground stake, attached to the fixture (8.5 in; 21.6 cm length)
- Warranty:** Lifetime warranty on fixture housing.

PAL105 Options:

Premium Black Overcoat
PAL105-BLK

LED LAMPS

E-LBIPIN-LED-250LM

BIPIN/G4 LED



SPECIFICATIONS AND FEATURES:

Base Type: G4/BiPin
Watts: 2.5
Light Output: 250 lumens
Color: Warm White
Color Temperatures: 2700K
Operating Voltage: 12v
CRI: >80
LED Chip Qty: 20 Pieces
Halogen Equivalent: 20w
Rated Hours: >25,000 hrs
Ambient Operating Temperature: -20°C - +50°C

E-LMR16-LED-5W-F

E-LMR16-LED-5W-F-4K

MR16 LED



SPECIFICATIONS AND FEATURES:

Base: MR16
Watts: 5.5
Beam Angle (Adjustable): 25° | 40° | 55°
Beam Spread: Narrow | Flood | Wide Flood
Light Output: 350 lumens
Color: Warm White
Color Temperature:
 2900K - (E-LMR16-LED-5W-F)
 4000K - (E-LMR16-LED-5W-F-4K)
Operating Voltage: 12v
CRI: Ra>80
LED Source: BRIDGELUX 3030
Halogen Equivalent: 35w
Rated Hours: 20,000 hrs
Ambient Operating Temperature: -15°C - 40°C

E-LMR16-LED-4W-F

MR16 LED



SPECIFICATIONS AND FEATURES:

Base: MR16
Watts: 4.5
Beam Angle (Adjustable): 25° | 40° | 55°
Beam Spread: Narrow | Flood | Wide Flood
Light Output: 250 lumens
Color: Warm White
Color Temperature: 2900K
Operating Voltage: 12v
CRI: Ra>80
LED Source: BRIDGELUX 3030
Halogen Equivalent: 20w
Rated Hours: 0,000 hrs
Ambient Operating Temperature: -15°C - 40°C

TRANSFORMERS

TF150

150 Watt Transformer Featuring:

- One 12 Volt tap only
- Built in photocell/timer
- DOE Compliant



TF200

200 Watt Stainless Steel Transformer

- One 12 Volt tap only
- Built in photocell/timer
- DOE Compliant

TF300

300 Watt Stainless Steel Transformer:

- Multiple Taps (12v-15v)
- Built in photocell/timer
- DOE Compliant

