

Type:

Model:

Project: _

WIRING: Pre-Installed 25' wire lead. Brown wire with aged brass finish,

WARRANTY: 10 year warranty on LED components and fixture housing.

CAN/CSA-C22.2 No. 250.7. Identified with the ETL & cETL Listed Mark.

CERTIFICATIONS: Complies with the requirements of UL-1838 and

MODEL: SL25-LED | INTEGRATED LED STEP LIGHT

Small professional-grade surface mounted step light. Classic louvered faceplate is ideal for illuminating steps and walkways while concealing the light source. Designed for installation in existing hardscapes such as stairs and walls, this fixture mounts flush to the surface and does not require or include a mudbox. Wood anchors are provided; for other surfaces, please select appropriate anchors. It is recommended to leave some slack in the wire to facilitate future maintenance.

black wire with black overcoat.

CONSTRUCTION: Solid cast brass face plate.

FINISH: Classic aged brass or modern premium black overcoat.

LENS: Louvered face plate.

LIGHT SOURCE: Integrated LED module pre-connected to the wire lead.

MOUNTING: Surface-mounted (backless), does not have/require a junction box.

DIMENSIONS:

Fixture Width	6 inches	
Fixture Height	2.88 inches	
Ship Weight	1.86 pounds	





Page 1 of 2

West Coast Hub: Temecula, CA • East Coast Hub: Sanford, FL Alliance Outdoor Lighting • (800) 930-6225 • www.allianceoutdoorlighting.com



MODEL: **SL25-LED** | INTEGRATED LED STEP LIGHT

FINISH OPTIONS:

Aged Brass (Standard)		
Premium Black Overcoat (Add -BLK)		

INTEGRATED LED MODULE DETAILS:

WATTS: 7W		
LUMENS: 570LM		
COLOR: Warm White		
COLOR TEMPERATURE: 2700K		
OPERATING VOLTAGE: 10 VAC - 15 VAC		
CRI : Ra>80		
RATED HOURS: 30,000 Hours		
AMBIENT OPERATING TEMPERATURE: ~40°C ~ +85°C		
DIMMING: None		





HOW TO SPECIFY: Example: SL25-LED-BLK

BASE PART #	FINISH	SUFFIX	ORDERING #
SL25-LED	Aged Brass (Standard)		SL25-LED
	Premium Black Overcoat	-BLK	SL25-LED-BLK

Page 2 of 2



West Coast Hub: Temecula, CA • East Coast Hub: Sanford, FL Alliance Outdoor Lighting • (800) 930-6225 • www.allianceoutdoorlighting.com 240506 Rev. 11/2024