

MODEL: LMR16-LED-4W-F | 4 WATT MR16 LED LAMP

Compact, low-voltage lamps favored for most outdoor lighting fixtures. Standard 4 watt lamp with 45° degree beam angle. Favored for directional illumination and weather-resistant design, ideal for highlighting landscaping and architectural features with precision. Optimal power efficiency and durability, making them a reliable choice for enhancing outdoor spaces. Produces a soft white light to accent your landscape.

CONSTRUCTION: Vented aluminum body and durable black plastic.

PINS: G4 bi-pin, dual contacts.

PASSIVE COOLING: Aluminum heatsink fins. Passive heat exchanger to transfer heat from device LED components to improve device performance and extend its life.

WARRANTY: Ten year warranty.

LED SOURCE: CREE XPE LED diodes delivers exceptional brightness and energy efficiency, making it an ideal for residential to commercial.


DIMENSIONS:

Height from top of pins to top of lamp _____ 1.56 inches

Width _____ 2 inches

Bi-Pins Length _____ 0.4375 inches

Ship Weight _____ 0.12 pounds



SPECIFICATIONS:

WATTS: 4 watts
BEAM ANGLE: 45° degrees
BEAM SPREAD: Flood
LIGHT OUTPUT: 250 lumens
COLOR: Warm White
COLOR TEMPERATURE: 2900K
OPERATING VOLTAGE: 12 - 14 volts
CRI: Ra>80
LED SOURCE: CREE XPE
HALOGEN EQUIVALENT: 20 watts
RATED HOURS: 50,000 hours
AMBIENT OPERATING TEMPERATURE: <72°C

