


**MODEL: LMR16-LED-4W-WF | 4 WATT MR16 LED LAMP**

Compact, low-voltage lamps favored for most outdoor lighting fixtures. Standard 4 watt lamp with wide flood, 60° degree beam angle. Favored for directional illumination and weather-resistant design, ideal for highlighting landscaping and architectural features with precision. Optimal power efficiency and durability, making them a reliable choice for enhancing outdoor spaces. Produces a soft white light to accent your landscape.

<b>CONSTRUCTION:</b> Vented aluminum body and durable black plastic.	<b>PINS:</b> G4 bi-pin, dual contacts.
<b>PASSIVE COOLING:</b> Aluminum heatsink fins. Passive heat exchanger to transfer heat from device LED components to improve device performance and extend its life.	<b>WARRANTY:</b> Ten year warranty.
<b>LED SOURCE:</b> CREE XPE LED diodes delivers exceptional brightness and energy efficiency, making it an ideal for residential to commercial.	

**DIMENSIONS:**

- Height from top of pins to top of lamp \_\_\_\_\_ 1.56 inches
- Width \_\_\_\_\_ 2 inches
- Bi-Pins Length \_\_\_\_\_ 0.4375 inches
- Ship Weight \_\_\_\_\_ 0.12 pounds



**SPECIFICATIONS:**

<b>WATTS:</b> 4 watts
<b>BEAM ANGLE:</b> 60° degrees
<b>BEAM SPREAD:</b> Wide Flood
<b>LIGHT OUTPUT:</b> 250 lumens
<b>COLOR:</b> Warm White
<b>COLOR TEMPERATURE:</b> 2900K
<b>OPERATING VOLTAGE:</b> 12 - 14 volts
<b>CRI:</b> Ra>80
<b>LED SOURCE:</b> CREE XPE
<b>HALOGEN EQUIVALENT:</b> 20 watts
<b>RATED HOURS:</b> 50,000 hours
<b>AMBIENT OPERATING TEMPERATURE:</b> <72°C

