

ALLIXNCE OUTDOOR LIGHTING		
Specification Sheet		

Type:	
,,	
Model:	
Project:	

## MODEL: LMR16-LED-5W-WF | 5 WATT MR16 LED LAMP

Compact, low-voltage lamps favored for most outdoor lighting fixtures. Standard 5 watt lamp with 60° degree beam angle. Favored for directional illumination and weather-resistant design, ideal for highlighting landscaping and architectural features with precision. Optimal power efficiency and durability, making them a reliable choice for enhancing outdoor spaces. Produces a soft white light to highlight the key features of your landscape.

**CONSTRUCTION:** Vented aluminum body and durable black plastic.

PASSIVE COOLING: Aluminum heatsink fins. Passive heat exchanger to transfer heat from device LED components to improve device performance and extend its life.

LED SOURCE: CREE XPE LED diodes delivers exceptional brightness and energy efficiency, making it an ideal for residential to commercial.

PINS: G4 bi-pin, dual contacts.

WARRANTY: Ten year warranty.

## **DIMENSIONS:**

Height from top of pins to top of lamp	1.56 inches
Width —	2 inches
Bi-Pins Length —	0.4375 inches
Ship Weight	0.12 pounds

## **SPECIFICATIONS:**

WATTS: 5 watts
BEAM ANGLE: 60° degrees
BEAM SPREAD: Wide Flood
LIGHT OUTPUT: 310 lumens
COLOR: Warm White
COLOR TEMPERATURE: 2900K
OPERATING VOLTAGE: 12 - 14 volts
CRI: Ra>80
LED SOURCE: CREE XPE
HALOGEN EQUIVALENT: 35 watts
RATED HOURS: 50,000 hours
AMBIENT OPERATING TEMPERATURE: <72°C







