

Type: _____

Model: _____

Project: _____

MODEL: E-LMR16-LED-5W-4K | PRO SERIES ADJUSTABLE MR16 LAMP

Compact, low-voltage lamps favored for most outdoor lighting fixtures. Standard 5 watt lamp with three adjustable beam spread options: narrow spot, flood, and wide flood. Favored for directional illumination and weather-resistant design, ideal for highlighting landscaping and architectural features with precision. Optimal power efficiency and durability, making them a reliable choice for enhancing outdoor spaces. Produces a cool white light to accent areas of most importance to your landscape.

CONSTRUCTION: Enclosed aluminum body and durable white plastic

PINS: G4 bi-pin dual contacts.

PASSIVE COOLING: Aluminum heatsink fins. Passive heat exchanger to transfer heat from device LED components to improve device performance and extend its life.

WARRANTY: 10 year warranty.

LED SOURCE: BRIDGELUX 3030 LED diodes delivers exceptional brightness and energy efficiency, making it an ideal lamp for residential to commercial.


DIMENSIONS:

Height from top of pins to top of lamp: _____ 1.56 inches

Width: _____ 2 inches

Bi-pins length: _____ 0.4375 inches

Ship Weight: _____ 0.12 lbs



SPECIFICATIONS:

WATTS:	5.5W
COLOR:	Cool White
COLOR TEMPERATURE:	4000K
LUMENS:	350lm
BEAM ANGLE:	25°, 40°, 55°
DIMMING:	None
OPERATING VOLTAGE:	12 volts
CRI:	Ra>80
LED SOURCE:	BRIDGELUX 3030
HALOGEN EQUIVALENT:	35 watts
RATED HOURS:	20,000 hours
AMBIENT OPERATING TEMP:	-15°C - 40°C

