

Type: \_\_\_\_\_

Model: \_\_\_\_\_

Project: \_\_\_\_\_

### MODEL: E-LMR16-LED-5W | PRO SERIES ADJUSTABLE MR16 LAMP

Compact, low-voltage lamps favored for most outdoor lighting fixtures. Standard 5 watt lamp with three adjustable beam spread options: narrow spot, flood, and wide flood. Favored for directional illumination and weather-resistant design, ideal for highlighting landscaping and architectural features with precision. Optimal power efficiency and durability, making them a reliable choice for enhancing outdoor spaces. Produces a soft white light to accent areas of most importance to your landscape.

**CONSTRUCTION:** Enclosed aluminum body and durable white plastic

**PINS:** G4 bi-pin dual contacts.

**PASSIVE COOLING:** Aluminum heatsink fins. Passive heat exchanger to transfer heat from device LED components to improve device performance and extend its life.

**WARRANTY:** 10 year warranty.

**LED SOURCE:** BRIDGELUX 3030 LED diodes delivers exceptional brightness and energy efficiency, making it an ideal lamp for residential to commercial.


#### DIMENSIONS:

Height from top of pins to top of lamp: \_\_\_\_\_ 1.56 inches

Width: \_\_\_\_\_ 2 inches

Bi-pins length: \_\_\_\_\_ 0.4375 inches

Ship Weight: \_\_\_\_\_ 0.12 lbs



#### SPECIFICATIONS:

<b>WATTS:</b>	5.5W
<b>COLOR:</b>	Soft White
<b>COLOR TEMPERATURE:</b>	2900K
<b>LUMENS:</b>	350lm
<b>BEAM ANGLE:</b>	25°, 40°, 55°
<b>DIMMING:</b>	None
<b>OPERATING VOLTAGE:</b>	12 volts
<b>CRI:</b>	Ra>80
<b>LED SOURCE:</b>	BRIDGELUX 3030
<b>HALOGEN EQUIVALENT:</b>	35 watts
<b>RATED HOURS:</b>	20,000 hours
<b>AMBIENT OPERATING TEMP:</b>	-15°C - 40°C

